SLENTITE®

The New High-Performance Insulation Board

Dr. Marc Fricke

Project Manager – High Performance Insulation Materials New Market Development BASF Polyurethanes GmbH, Lemfoerde









Existing Buildings





New Buildings



Driver:

Energetic retrofitting of historic buildings

Driver:

Lack of space, aesthetics

Thermal insulation materials help to save energy



We continue to innovate thermal insulation materials



R&D SLENTITE®


Game changer in thermal insulation




Knudsen effect

Aerogels

Far less contribution to thermal conductivity of the cell gas!





First quantities of polyurethanebased aerogel successful manufactured




New chemistries and process technologies for nanoporous materials developed



New chemical and physical concepts for high performance thermal insulation materials explored

Standard foams

Large contribution to thermal conductivity









- Lambda value of 17 mW/mK vs. industry standard of 21 to 40 mW/mK
- 25% 50% slimmer insulation vs. industry standard
- Compression strength of300 kPa, twice as good as today's PU insulation panels
- Open-pored structure ensures good moisture regulation

SLENTITE®: A unique high-performance product for the insulation sector



From pilot phase to production

Pilot plant, Lemfoerde

- Manufacture larger samples
- Scale up for production plant concept
- Joint development for marketreadiness with strategic partners
- Definition of business model

Finalization of production concept

Production

- Start of production
- In house production depending on business model decision

2015




2017











Neopor[®]

SLENTITE®

Joint presentation at Fairs Frontale and IEX 2016 with





We create chemistry